

Commercial Central Control Comparison Chart

iCentral ™

OASIS[™]

Key Software Features	Rain Master Eagle-i	Rain Master Eagle-i Plus	Evolution $_{\mathcal{D}X2}$
System Software	Internet Based	Internet Based	Computer Based
Software Subsciption Fees	As Low As \$120/yr	As Low As \$120/yr	1-Time Softeware Purch.
Yrs Included with Controller Purchase	1-Year of iCentral	2-Years of iCentral	Not Applicable
Irrigation Scheduling Engine	Simple and Advanced	Simple and Advanced	AdvancedET™
Daily ET Adjustments	ZipET™, CIMIS, Weather Station	ZipET™, CIMIS, Weather Station	CIMIS, and Weather Station
Real Time Alerts to Phone/Email	\checkmark	<	\checkmark
Real Time Reporting	\checkmark	<	\checkmark
Share a Rain Sensor/Weather Center	\checkmark	<	\checkmark
Ability to Share a Tipping Bucket	N/A	<	\checkmark
Auto Learn Flow	\checkmark	\checkmark	\checkmark
Communication Option(s)	Paging	GSM Cellular	Cellular, Radio, Wifi, Ethernet, Phone, Hardwire
Mobile Phone Access	\checkmark	\checkmark	N/A
Flow Sensing	\checkmark	\checkmark	\checkmark
Flow Management	N/A	N/A	\checkmark
Visual Positioning Map™	N/A	N/A	\checkmark
Real Time Weather VIEW™	N/A	N/A	\checkmark
"No Charge" Customer Service	Phone, and Online Support	Phone, and Online Support	Phone, and Online Support

Key Controller Features	Rain Master Eagle-i	Rain Master Eagle-i Plus	Evolution DX2
Conventional / Two-Wire Station Count	36 Conv, 36 Two-Wire	48 Conv, 200 Two-Wire	48 Conv, 48 Two-Wire
Number of Programs (Conv/Two-Wire)	4 /4	8/16	12 / 12 (or ISP)
Number of Start Times	5	8	8
Cycle and Soak Programming	\checkmark	\checkmark	\checkmark
Day Programming	7, Skip, Odd/Even	14, Skip, Odd/Even	14, 31, Skip, Odd/Even
Programmable Rain Delay	\checkmark	\checkmark	\checkmark
Rain/Freeze/Moisture Sensor Input	\checkmark	\checkmark	\checkmark
Weather Center Inputs	\checkmark	\checkmark	\checkmark
Advanced Electrical Fault Detection	\checkmark	\checkmark	\checkmark
Advanced Flow Sensing	\checkmark	\checkmark	\checkmark
Master Valve and Pump Control	\checkmark	\checkmark	\checkmark
Share Flow Sensor	Optional	Optional	✓ FloMax [™]
Built-in Pro Max Remote Interface	\checkmark	\checkmark	\checkmark
Transformer Maximum Load	1.5 AMPS	1.5 AMPS	2.0 AMPS
Warranty	5 Years	5 Years	2 Years